

celsure®

Temperature Controlled Packaging for Pharmaceuticals

celsure® Parcel Shippers | Single Use | Up to 120 hours

Model No.	Coolant Type	Backup (hrs.)	Ext. Dim. (mm)	Payload Dim. (mm)	Payload Vol. (ltr)	Vol. Wt. (kg)	Tare Wt. (kg)
Temperature Range: 2°C to 8°C and 15°C to 25°C							
7L4D-08P/7L4D-25P	Gel Pack + PCM	96 - 120	500 x 500 x 460	224 x 224 x 124	6	19	15
14L4D-08P/14L4D-25P	Gel Pack + PCM	96 - 120	540 x 540 x 520	282 x 294 x 152	13	25	22
28L4D-08P/28L4D-25P	Gel Pack + PCM	96 - 120	570 x 570 x 600	335 x 335 x 250	28	32	26
28L3D-08PS	All PCM	72 + hibernation	570 x 570 x 600	320 x 320 x 250	26	32	28
60L5D-08P/60L5D-25P	Gel Pack + PCM	96 - 120	675 x 675 x 675	385 x 385 x 385	57	51	50
60L3D-08PS	All PCM	72 + hibernation	675 x 675 x 675	385 x 385 x 385	57	51	42

Temperature Range: -25°C to -15°C							
7L5D-25N	All PCM	120 + hibernation	540 x 540 x 520	224 x 224 x 124	6	25	35
14L4D-25N	All PCM	96 + hibernation	540 x 540 x 520	259 x 259 x 199	13	25	34
28L4D-25N	All PCM	96 + hibernation	570 x 570 x 600	335 x 335 x 250	28	32	49
60L4D-25N	All PCM	96 + hibernation	675 x 675 x 675	385 x 385 x 385	57	51	68

Temperature Range: -80°C to -20°C							
14L5D-DI	Dry Ice	96 - 120	490 x 490 x 395	299 x 299 x 156	14	16	18
26L5D-DI	Dry Ice	96 - 120	523 x 523 x 435	325 x 325 x 250	26	20	27
35L5D-DI	Dry Ice	96 - 120	575 x 575 x 575	370 x 370 x 260	36	32	38

celsure[®] *express* Parcel Shippers | Single Use | Up to 72 hours

Model No.	Coolant Type	Backup (hrs.)	Ext. Dim. (mm)	Payload Dim. (mm)	Payload Vol. (ltr)	Vol. Wt. (kg)	Tare Wt. (kg)
Temperature Range: 2°C to 8°C and 15°C to 25°C							
4L2D-08P/4L2D-25P	Gel Pack + PCM	48 - 72	300 x 300 x 355	190 x 115 x 195	4	5	4
7L2D-08P/7L2D-08P	Gel Pack + PCM	48 - 72	490 x 490 x 395	224 x 224 x 124	6	16	11
14L2D-08P/14L2D-25P	Gel Pack + PCM	48 - 72	525 x 525 x 435	282 x 294 x 152	13	20	11
28L2D-08P/28L2D-25P	Gel Pack + PCM	48 - 72	575 x 575 x 575	335 x 335 x 250	28	32	19
35L4D-25P	Gel Pack + PCM	48 - 72	640 x 450 x 480	515 x 350 x 190	34	23	19

Temperature Range: -25°C to -15°C							
3L1D-25N	All PCM	27 + hibernation	300 x 300 x 355	194 x 115 x 115	3	5	7
7L2D-25N	All PCM	48 + hibernation	490 x 490 x 395	224 x 224 x 124	6	16	17
14L2D-25N	All PCM	48 + hibernation	540 x 540 x 450	259 x 259 x 199	13	22	25
28L2D-25N	All PCM	48 + hibernation	575 x 575 x 575	335 x 335 x 250	28	32	32

celsure[®] *2* EARTH Recyclable Parcel Shippers | Single Use | Up to 48 hours

Model No.	Coolant Type	Backup (hrs.)	Ext. Dim. (mm)	Payload Dim. (mm)	Payload Vol. (ltr)	Vol. Wt. (kg)	Tare Wt. (kg)
Temperature Range: 2°C to 8°C and 15°C to 25°C							
10L2D-08P/10L2D-25P	Gel Pack + PCM	48	505 x 395 x 415	300 x 240 x 150	10	14	11
35L2D-08P/35L2D-25P	Gel Pack + PCM	48	660 x 510 x 430	520 x 355 x 195	35	24	22

PLUSS[®] | TECHNOLOGY FOR A BETTER WORLD


murugappa


CUMI

CELSURE ^{VIP} High Performance Parcel Shippers | Multi Use | Up to 120 hours

Model No.	Coolant Type	Backup (hrs.)	Ext. Dim. (mm)	Payload Dim. (mm)	Payload Vol. (ltr)	Vol. Wt. (kg)	Tare Wt. (kg)
Temperature Range: 2°C to 8°C							
8L3D-08PSR	All PCM	72 + hibernation	365 x 305 x 310	196 x 196 x 196	8	6	8
11L5D-08PSR	All PCM	120 + hibernation	415 x 365 x 380	222 x 222 x 222	11	10	16
27L5D-08PSR	All PCM	120 + hibernation	450 x 450 x 455	300 x 300 x 300	27	15	26
Temperature Range: 15°C to 25°C							
8L4D-25PR	All PCM	72 + hibernation	365 x 305 x 310	196 x 196 x 196	8	6	8
11L5D-25PR	All PCM	120 + hibernation	415 x 365 x 380	222 x 222 x 222	11	10	17
27L5D-25PR	All PCM	120 + hibernation	450 x 450 x 455	300 x 300 x 300	27	15	20
Temperature Range: -25°C to -15°C							
8L3D-25NR	All PCM	48 + hibernation	365 x 305 x 310	196 x 196 x 196	8	6	10
11L5D-25NR	All PCM	120 + hibernation	415 x 365 x 380	222 x 222 x 222	11	10	21
27L5D-25NR	All PCM	120 + hibernation	450 x 450 x 455	300 x 300 x 300	27	15	33



Pallet Shippers | Single Use | Up to 120 hours

Model No.	Coolant Type	Backup (hrs.)	Ext. Dim. (mm)	Payload Dim. (mm)	Payload Vol. (ltr)	Vol. Wt. (kg)	Tare Wt. (kg)
Temperature Range: 2°C to 8°C							
130L4D-08P (Drum Shipper)	Gel Pack + PCM	96-120	730 x 730 x 1260	450 x 450 x 630	130	112	80
140L3D-08PS (Drum Shipper)	All PCM	72 + hibernation	730 x 730 x 1260	450 x 450 x 705	140	112	60
200L5D-08P	Gel Pack + PCM	96 - 120	1200 x 800 x 965	970 x 570 x 360	200	154	92
260L3D-08PS	All PCM	72 + hibernation	1200 x 800 x 965	954 x 550 x 510	270	154	65
330L5D-08P	Gel Pack + PCM	96 - 120	1200 x 800 x 1265	974 x 574 x 590	330	202	138
400L3D-08PS	All PCM	72 + hibernation	1200 x 800 x 1265	970 x 570 x 705	390	202	100
1200L5D-08P	Gel Pack	96 - 120	1565 x 1190 x 1450	1265 x 890 x 1020	1148	450	240
1200L3D-08PS	All PCM	72 + hibernation	1565 x 1190 x 1450	1265 x 890 x 1020	1148	450	220
1200L4D-08PS	All PCM	96 + hibernation	1565 x 1190 x 1450	1265 x 890 x 970	1092	450	250
1600L3D-08PS	All PCM	72 + hibernation	1565 x 1375 x 1590	1265 x 1075 x 1180	1604	570	220
1600L4D-08PS	All PCM	96 + hibernation	1565 x 1375 x 1590	1265 x 1075 x 1130	1537	570	252
1600L5D-08PSR	All PCM	120 + hibernation	1400 x 1220 x 1530	1220 x 1040 x 1260	1599	436	235
3000L3D-08PS	All PCM	72 + hibernation	2398 x 1565 x 1590	2098 x 1265 x 1130	3000	995	419
3000L4D-08PS	All PCM	96 + hibernation	2398 x 1565 x 1590	2098 x 1265 x 1130	3000	995	490
Temperature Range: 15°C to 25°C							
170L5D-25P (Drum Shipper)	All PCM	120 + hibernation	730 x 730 x 1260	450 x 450 x 850	172	112	40
290L5D-25P	All PCM	120 + hibernation	1200 x 800 x 965	970 x 570 x 525	290	154	60
400L5D-25P	All PCM	120 + hibernation	1200 x 800 x 1265	970 x 570 x 705	390	202	90
1200L5D-25P	All PCM	120 + hibernation	1565 x 1190 x 1450	1265 x 890 x 1020	1148	450	150
1600L5D-25P	All PCM	120 + hibernation	1565 x 1375 x 1590	1265 x 1075 x 1180	1604	570	220
3000L5D-25P	All PCM	120 + hibernation	2398 x 1565 x 1590	2098 x 1265 x 1130	3000	995	237
Temperature Range: -25°C to -15°C							
130L4D-25N (Drum Shipper)	All PCM	96 + hibernation	730 x 730 x 1260	450 x 450 x 630	130	112	80
200L5D-25N	All PCM	96 + hibernation	1200 x 800 x 965	970 x 570 x 360	200	154	170
330L5D-25N	All PCM	96 + hibernation	1200 x 800 x 1265	970 x 570 x 590	330	202	226
1200L4D-25N	All PCM	96 + hibernation	1565 x 1190 x 1450	1265 x 890 x 1020	1148	450	295
1600L4D-25N	All PCM	96 + hibernation	1565 x 1375 x 1590	1265 x 1075 x 1130	1537	570	310
3000L4D-25N	All PCM	96 + Hibernation	2398x1565x1590	2098x1265x1130	3000	995	605